

DUMP TRAILER GUIDE



DUMPS: (D5), (D3)

LOW-PRO: (DL), (DM) | DECKOVERS: (D8), (DD)

ROLL-OFF: (DR), (KD), (RD)



THE PROFESSIONAL GRADE STANDARD

THE PROFESSIONAL GRADE STANDARD

PJ Trailers is the industry leader when it comes to combining product quality, support, and level of personal customization. We sell our trailers through a nation-wide network of individual dealers, ready to outfit you with a custom trailer that meets your needs and support you afterwards. Each of our trailer categories is built with quality components as standard, like lifetime-warranty LED lights, heavy-duty running gear and a three-year frame warranty. The entire build process is designed to ensure your trailer is in service for years to come and functions with the flow of your business or recreational activities. This commitment to our customers means we're a partner you can count on, rain or shine. Ask your local PJ Trailers dealer today about ordering your very own customized PJ Trailer.



ROLLSTER™

ROLL-OFF DUMP (DR)..... 4
ROLL-OFF BIN (KD) & ROLL-OFF DECK (RD)..... 5

DUMPS

60" UTILITY DUMP (D5) 6
72" TANDEM AXLE DUMP (D3)..... 7

LOW-PRO DUMPS

83" LOW-PRO DUMP (DL) 8
83" LOW-PRO HIGH SIDE DUMP (DM) 9

DECKOVER DUMPS

96" DECKOVER DUMP (D8) 10
TANDEM DUAL DUMP (DD)..... 11





ROLLSTER™ | ROLL-OFF DUMP (DR)

Lengths: 14'



6" CHANNEL FRAME

Length	Axles	Est. Base Weight†
14'	2 x 7,000 lbs	6,280 lbs /2,849 kg

† Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.



Rated at 17,500 lbs., this Smittybilt X20 heavy-duty winch features an all-new 6.6HP waterproof motor that offers the highest torque in the industry and connects to a 3-stage Planetary Gear System for increased pulling power and line speed.

STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Spring Loaded Drop Leg Jack (10,000 lb)
- 2 - Dexter E- Z lube Brake Axle (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 1/8" Treadplate Steel Fenders
- Lockable Toolbox (Houses Battery and Pump)
- Barn Door Gates
- 4 - D-Rings (Welded inside the Box)
- 45° Dump Pitch
- 12VDC Hydraulic Pump
- 5" x 17" Hyd. Cylinder w/Scissor Lift
- Scissor Lift
- 12' Control Cable
- BED Mounted 84" X 20' Heavy-Duty UV resistant Tarp
- 6" Channel Main Frame & Tongue
- 2" x 6" x 11ga. Tubing Bed Frame
- 3" Channel Crossmembers 16" on Center
- 10-ga. Steel Bed
- 83" Wide Bed
- 10-ga. Steel Sides
- 48" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- 2 - Power Volt Group 27 Batteries
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped w/Lockable Front Toolbox
- 5 year Dexter Axle Warranty
- 17.5 Smittybilt Winch

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/8" Adjustable (14,000 lb.)*
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- BP 2 5/8" Adj. Cplr w/HD 6 hole Chn Brkt (20k)
- GN 2 5/8" Round (25,000 lb.)
- GN 2 5/8" Square (25,000 lb.)

AXLE OPTIONS

7,000# (DEXTER)

- (2) Electric (Spring)*

7,000# W/ 14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)

8,000# OIL BATH W/ 14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)

TAIL OPTIONS

- Straight Deck*

OTHER OPTIONS

- Upgrade to Black Spoke Wheels (15-16" Wheels Only)
- 1 - Roll Off Dump w/Barn Door
- 2 - 1 - Roll Off Dump w/Barn Door
- 3 - 1 - Roll Off Dump w/Barn Door
- 4 - 1 - Roll Off Dump w/Barn Door
- 5 - 1 - Roll Off Dump w/Barn Door
- Bulldog 2-speed Jacks (12,000 lb.)



IN-FRAME ROLLERS

Our 3" in-frame greasable rollers reduce friction and maximize battery life, giving you more loads/unloads between having to recharge.



DUAL BATTERIES

With a dual battery setup, these PowerVolt industrial deep-cycle batteries are perfectly suited for maximum load applications! Rated with a higher amp hour, these Group 27 batteries will give you more loads and unloads in the field.



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Construction, roofing, landscaping and other similar industries have demanding waste removal needs. These tough jobs require durable, hardy bins and reliable trailers that not only get the work done, but also create solutions for the problems you face – problems such as preventing trailer theft while, at the same time, boosting your productivity as you serve multiple job-sites.

Once you drop your bin, your trailer is able to serve multiple job-sites. By investing in multiple bins and decks rather than multiple trailers, your overhead is reduced and efficiency improved. Additionally, the Rollster™ can also function just like a traditional dump trailer.



ROLL-OFF BIN (KD)

- Mounted 84' x 20' heavy-duty UV resistant tarp
- 83" dump bed width
- 13.26 cubic yard capacity (14 ft w/ 48" sides)
- Heavy-duty 10-gauge sides
- 12-gauge side reinforcement supports
- 4 - D-Rings
- Barn door gates
- Heavy duty 10-gauge dump bed floor
- 3" channel on 16" centers dump bed crossmembers
- 5" x 9" greasable rollers



ROLL-OFF DECK (RD)

- 14' x 96" deck area
- 3" channel 77" x 16" slide in ramps
- Front bump stop
- 3" C-Channel crossmembers on 16" centers
- 4 - D-Rings
- Rub rail with stake pockets
- No. 2 Treated Southern Yellow Pine
- 5" x 9" greasable rollers





60" UTILITY DUMP (D5)

Lengths: 8' - 10'



Tandem Axle Option Shown (Single Axle Standard)

4" CHANNEL FRAME

Length	Axles	Est. Base Weight†
8'	1 x 5,200 lbs	1,800 lbs / 816 kg
10'	1 x 5,200 lbs	2,020 lbs / 916 kg
10'	2 x 3,500 lbs	2,200 lbs / 998 kg

† Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **5,200 - 9,990 LBS.** ■ AXLE: **SINGLE & TANDEM (1-2 X 3,500 - 7,000 LBS. AXLES)**
- LENGTH: **8-10'** ■ CAPACITY: **2.22 - 2.78 YD³**
- SIDES HEIGHT: **18"** ■ INSIDE WIDTH: **60"** ■ BED HEIGHT: **26"** ■ DUMP ANGLE: **40°**
- COUPLERS: **BUMPER PULL & PINTLE** ■ TIRES: **225/75B15 TIRES**

STANDARD FEATURES

- 5,200 lb. G.V.W.R.
- 5,200 lb. x 1 G.A.W.R.
- 2" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 1 - Dexter E-Z Lube Brake Axle (5,200 lb.)
- 6 Leaf Double-eye Spring Suspension
- 2 - 15" White Spoke Wheels
- 2 - ST225/75B15 (2540 lb)
- Electric Breakaway Kit w/ Charger
- 1/8" Treadplate Steel Fenders
- Lockable Toolbox (Houses Battery and Pump)
- Barn Door Gate w/ Camlatch
- 4 - D-Rings
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 3" x 30" Hyd. Cylinder
- 12' Control Cable
- 4" Channel Main Frame & Tongue
- 2" x 4" x 11ga. Tubing Bed Frame
- 3" Channel Crossmembers 16"oc
- Mounting Brackets for Roll-up Tarp
- 10-ga. Steel Bed
- 5' Wide Bed
- 10-ga. Steel Sides
- 18" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- 2" A-Frame (7,000 lb.)*
- BP 2 5/16" Adjustable (14,000 lb.)
- 3" Pintle Eye - Channel-mount (21,000 lb.)

AXLE OPTIONS

3,500# (DEXTER)

- (2) Electric (Spring)
- (2) Surge Hydraulic Drum [Surge Coupler] (Spring)

5,200# (DEXTER)

- (1) Electric (Spring)*
- (1) Surge Hydraulic Drum [Surge Coupler] (Spring)
- (2) Electric (Spring)
- (2) Surge Hydraulic Drum [Surge Coupler] (Spring)

TAIL OPTIONS

- Split Gate*
- Split / Spreader Gate

OTHER OPTIONS

- 1 Pair D-Rings
- Solar Battery Charger
- Upgrade to 235/80 R16 on 52k Axles (Tandem Only)
- 12"oc Crossmembers
- Mount Only for Spare Tire
- Tarp kit (Pull Bar) 5 x 14ft
- Ramps
- Spare Tire and Mount
- 18" Side Extensions (Expanded Metal)
- 18" Side Extensions



10-GAUGE SIDES & FLOOR

We use one-piece, 10-gauge sides and floors on all our dump beds and non-folding dump sides. This material resists warping between crossmembers, and the single central weld enhances unloading.



PREMIUM HYDRAULIC SYSTEMS

A dump trailer is only as good as its hydraulic components, and we choose to use the finest parts available. Our pumps are shielded in a steel locking toolbox for protection against the elements.



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

72" TANDEM AXLE DUMP (D3)



Lengths: 10' - 12'



5" CHANNEL FRAME

Length	Axles	Est. Base Weight†
10'	2 x 5,200 lbs	2,520 lbs / 1,143 kg
12'	2 x 5,200 lbs	3,020 lbs / 1,370 kg

† Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **9,990 LBS.** ▪ AXLE: **TANDEM (2 X 3,500 - 7,000 LBS. AXLES)**
- LENGTH: **10' & 12'** ▪ CAPACITY: **3.7 - 4.44 YD³**
- SIDES HEIGHT: **20"** ▪ INSIDE WIDTH: **72"** ▪ BED HEIGHT: **28"** ▪ DUMP ANGLE: **40°**
- COUPLERS: **BUMPER PULL & PINTLE** ▪ TIRES: **225/75R15 RADIAL TIRES**

STANDARD FEATURES

- 9,900 lb. G.V.W.R.
- 5,200 lb. x 2 G.A.W.R.
- 2 5/16" A Frame Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Dexter E- Z Lube Brake Axle (5,200 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 15" White Spoke Wheels
- 4 - 225/75R15 Radial Tires (lb.)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Treadplate Steel Fenders
- Toolbox
- Barn Door Gate
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 5" x 30" Hyd. Cylinder
- 12' Control Cable
- 5" Channel Main Frame & Tongue
- 16" On Center 3" Channel Crossmembers
- 10-ga. Steel Bed
- 72" Wide Bed
- 20" 10ga Steel Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" A-Frame (12,500lb.)*
- BP 2 5/16" Adjustable (14,000 lb.)
- 3" Pintle Eye - Channel-mount (21,000 lb.)

AXLE OPTIONS

5,200# (DEXTER)

- (2) Electric (Spring)*
- (2) Surge Hydraulic Drum [Surge Coupler] (Spring)

TAIL OPTIONS

- Split Gate*
- Split / Spreader Gate

OTHER OPTIONS

- 1 Pair D-Rings
- Upgrade to (1) - Single BULLDOG 10k Jack
- No Tarp Mounting Brackets
- Rear Support Stands

- Upgrade to 235/80 R16 on 52k Axles
- Upgrade to Single 10k Jack (Bumper Pull)
- Solar Battery Charger
- 12"oc Crossmembers
- Power Up/Down & Gravity Down Upgrade
- Mount Only for Spare Tire
- Tarp kit (Pull Bar) 6 x 14ft
- Ramps w 4 D-Rings
- Spare Tire and Mount (Bumper Pull)



SELF CONTAINED HYDRAULIC UNIT & LOCKING FRONT TOOLBOX

Our dumps feature a self contained power unit, securely mounted in a solid steel locking front toolbox.



FORMED STEEL SIDE SUPPORTS & DIAMOND PLATE FENDERS

Our formed steel side supports add significant strength to the dump bed. Our D3 Dump also comes with super durable steel diamond plate fenders.



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.



83" LOW-PRO DUMP (DL)

Lengths: 12' - 16'



8" I-BEAM FRAME

LOW-PRO DECK HEIGHT

Ultra-Low 24" Bed Height Available:
Choose Optional 7K Dexter Electric Drop Axles to Provide an Ultra-Low 24" Bed Height

Length	Axles	Est. Base Weight†
12'	2 x 7,000 lbs	3,880 lbs / 1,760 kg
14'	2 x 7,000 lbs	4,340 lbs / 1,969 kg
16'	2 x 7,000 lbs	4,665 lbs / 2,116 kg

† Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **14,000-16,000 LBS.** ■ AXLE: **TANDEM (2 X 7,000 AXLE)**
- LENGTH: **12-16'** ■ CAPACITY: **6.15 YD³ - 8.20 YD³**
- SIDES HEIGHT: **24"** ■ INSIDE WIDTH: **83"** ■ BED HEIGHT: **24-28"** ■ DUMP ANGLE: **40°**
- COUPLERS: **BUMPER PULL, GOOSENECK & PINTLE** ■ TIRES: **235/80R16 RADIAL TIRES**

STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Dexter E-Z lube Brake Axle (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 1/8" Treadplate Steel Fenders
- Lockable Toolbox (Houses Battery and Pump)
- 2 - Way Gate (Barn Doors & Spread Gate)
- 6' 6" Slide In Channel Ramps
- 4 - D-Rings (Welded inside the Box)
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 5"x17" Hyd.Cylinder w/Scissor & 5"x 21" on 16'
- Scissor Lift
- 12" Control Cable
- Mounting Brackets for Roll-up Tarp
- 8" x 10 lb. I-Beam Frame & Tongue
- 3" Channel Crossmembers 16" on Center
- 10-ga. Steel Bed
- 83" Wide Bed
- 10-ga. Steel Sides
- 24" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Stake Pockets
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- Ultra Low 24"- 28" Deck Height
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped w/Lockable Front Toolbox
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" Adjustable (14,000 lb.)*
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- BP 2 5/16" Adj. Cplr w/HD 6 hole Chn Brkt (20k)
- GN 2 5/16" Round (25,000 lb.)
- GN 2 5/16" Square (25,000 lb.)
- GN 2 5/16" Round (30,000 lb.) w/ 6" Longer Tube

AXLE OPTIONS

7,000# (DEXTER)

- (2) Electric (Spring)*
- (2) Electric (Drop Axle)

7,000# W/215/75R17.5 LR-H SINGLES (DEXTER)

- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

7,000# W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Drop Axle)
- (2) Electric (Spring)

8,000# OIL BATH W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)

TAIL OPTIONS

Split / Spreader Gate*

OTHER OPTIONS

- 1 Extra Battery
- Removable Deck on the Neck (102" Wide 96" Long)
- 1 Pair D-Rings

- Fork Rack
- 1 Hydraulic Monster Jack™ Includes Front Toolbox
- Rear Support Stands
- Spare Tire & Mount (Bumper Pull) G Rated 215/75/R17.5 (H) 8k Axle Spare Tire and Mount
- Spare Tire and Mount (BP) 215/75/R17.5
- 7 Gauge Solid Metal Sides & Floor
- Top Riser Toolbox
- Upgrade to Single 10k Jack (Bumper Pull)
- Solar Battery Charger
- 6" Taller GN Riser
- Full Size Divided Toolbox Upgrade (BP Only) 9,990 G.V.W.R.
- 12"oc Crossmembers
- Power Up/Down & Gravity Down Upgrade
- HD 24" Side Extensions 10ga
- Mount Only for Spare Tire
- Tarp kit(Pull Bar)7x20ft
- Spare Tire and Mount (Bumper Pull)
- 24" Side Extensions (Expanded Metal)
- Bulldog 2-speed Jacks (12,000 lb.)
- 24" Side Extensions (Solid)



10 GAUGE SIDES & FLOOR

We use one-piece, 10-gauge sides and floors on all our dump beds and non-folding dump sides. This material resists warping between crossmembers, and the single central weld enhances unloading.

8" I-BEAM



8" HD I-BEAM FRAME

The DL & DM dump features a heavy duty 8" I-beam frame for maximum strength, backed our 3-year frame warranty.

83" LOW-PRO HIGH SIDE DUMP (DM)



Lengths: 12' - 16'



8" I-BEAM FRAME

Length	Axles	Est. Base Weight†
12'	2 x 7,000 lbs	4,870 lbs / 2,209 kg
14'	2 x 7,000 lbs	5,180 lbs / 2,350 kg
16'	2 x 7,000 lbs	5,720 lbs / 2,595 kg

† Weights are estimated for base trailer.

PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **14,000-16,000 LBS.** ▪ AXLE: **TANDEM (2 X 7,000 AXLE)**
- LENGTH: **12-16'** ▪ CAPACITY: **9.22 YD³ - 16.40 YD³**
- SIDES HEIGHT: **36" & 48"** ▪ INSIDE WIDTH: **83"** ▪ BED HEIGHT: **24-28"** ▪ DUMP ANGLE: **40°**
- COUPLERS: **BUMPER PULL, GOOSENECK & PINTLE** ▪ TIRES: **235/80R16 RADIAL TIRES**

LOW-PRO
DECK HEIGHT

Ultra-Low 24" Bed Height Available:
Choose Optional 7K Dexter Electric Drop Axles
to Provide an Ultra-Low 24" Bed Height

STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Dexter E-Z lube Brake Axle (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 1/8" Treadplate Steel Fenders
- Lockable Toolbox (Houses Battery and Pump)
- 2 - Way Gate (Barn Doors & Spread Gate)
- 6' 6" Slide In Channel Ramps
- 4 - D-Rings (Welded inside the Box)
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 5"x17" Hyd.Cylinder w/Scissor & 5"x 21" on 16'
- Scissor Lift
- 12' Control Cable
- Mounting Brackets for Roll-up Tarp
- 8" x 10 lb. I-Beam Frame & Tongue
- 3" Channel Crossmembers 16" on Center
- 10-ga. Steel Bed
- 83" Wide Bed
- 10-ga. Steel Sides
- 48" High Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Stake Pockets
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- Ultra Low 24"- 28" Deck Height
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped w/Lockable Front Toolbox
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" Adjustable (14,000 lb.)*
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- BP 2 5/16" Adj. Cplr w/HD 6 hole Chn Brkt (20k)
- GN 2 5/16" Round (25,000 lb.)
- GN 2 5/16" Square (25,000 lb.)
- GN 2 5/16" Round (30,000 lb.) w/ 6" Longer Tube

AXLE OPTIONS

7,000# (DEXTER)

- (2) Electric (Spring)*
- (2) Electric (Drop Axle)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

7,000# W/215/75R17.5 LR-H SINGLES (DEXTER)

- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

7,000# W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Drop Axle)
- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

8,000# OIL BATH W/215/75R17.5 LR-H SINGLES(-DEXTER)

- (2) Electric (Spring)

8,000# OIL BATH W/14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)

TAIL OPTIONS

- Split / Spreader Gate*

OTHER OPTIONS

- 1 Extra Battery
- 1 Pair D-Rings
- Fork Rack
- HD 25k Jost 2x Jacks
- 1 Hydraulic Monster Jack™ Includes Front Toolbox
- 2 Hydraulic Monster Jacks™
- Upgrade to (1) - Single BULLDOG 10k Jack
- Upgrade to (2) - Dual BULLDOG 10k Jacks (GN Only)
- Rear Support Stands
- 3ft Tall Sides
- Top Riser Toolbox
- Upgrade to Single 10k Jack (Bumper Pull)
- Solar Battery Charger
- 6" Taller GN Riser
- Full Size Divided Toolbox Upgrade (BP Only)
- 9,990 G.V.W.R.
- 12"oc Crossmembers
- Power Up/Down & Gravity Down Upgrade
- HD 24" Side Extensions 10ga
- Mount Only for Spare Tire
- Tarp kit(Pull Bar)
- Spare Tire and Mount (Bumper Pull)
- Bulldog 2-speed Jacks (12,000 lb.)
- 24" Side Extensions (Solid)



ULTRA-LOW 24" DUMP BED HEIGHT

The DL & DM's optional 24" deck height allows for a 14° load angle, making equipment hauling even easier. It also lowers the center of gravity for improved towing.



3' OR 4' HIGH SIDES

Our 3 & 4 ft high sides give you the extra space to safely carry bulky loads like brush and scrap metal without the need for side extensions.



96" DECKOVER DUMP (D8)

Lengths: 14-16'



Length	Axles	Est. Base Weight†
14'	2 x 7,000 lbs	4,100 lbs / 1,860 kg
14' (GN)	2 x 7,000 lbs	4,500 lbs / 2,041 kg

† Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **14,000-16,000 LBS.** ▪ AXLE: **TANDEM (2 X 7-8,000 LBS. AXLE)**
- LENGTH: **14-16'** ▪ CAPACITY: **6.57 YD³ - 7.51 YD³**
- SIDES HEIGHT: **19"** ▪ INSIDE WIDTH: **96"** ▪ BED HEIGHT: **34"** ▪ DUMP ANGLE: **40°**
- COUPLERS: **BUMPER PULL, GOOSENECK & PINTLE** ▪ TIRES: **235/80R16 RADIAL TIRES**

STANDARD FEATURES

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- Adjustable 2 5/16" Ball Bulldog Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Dexter E-Z lube Brake Axle (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Lockable Toolbox (Houses Battery and Pump)
- 2 - Way Gate (Barn Doors & Spread Gate)
- 80" Slide In Channel Ramps
- 4 - D-Rings
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- 5" x 17" Hyd. Cylinder w/Scissor Lift
- 12' Control Cable
- 6" Channel Tongue
- 8" I-Beam Main Frame
- Mounting Brackets for Roll-up Tarp
- 11ga. Fabricated Bed Frame
- 3" Channel Crossmembers 16" on Center
- 2" x 6" x 11ga. Tubing Outer Bed Frame
- 10-ga. Steel Bed
- 96" Wide Bed
- 12ga. Steel Sides
- 19" High Fold Down Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- GN Option Equipped with 2 Jacks
- GN Equipped w/Lockable Front Toolbox
- Under Frame Spare Mount on Bumperpulls w/Spare Opt
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" Adjustable (14,000 lb.)*
- 3" Pintle Eye - Channel-mount (20,000 lb.)
- GN 2 5/16" Round (25,000 lb.)
- GN 2 5/16" Square (25,000 lb.)
- GN 2 5/16" Round (30,000 lb.) w/ Toolbox

AXLE OPTIONS

7,000# (DEXTER)

- (2) Electric (Spring)*
- (3) Electric (Spring)

7,000# W/ 14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (3) Electric (Spring)

8,000# OIL BATH W/ 14 PLY LR-G TIRES (DEXTER)

- (2) Electric (Spring)
- (3) Electric (Spring)

8,000# OIL BATH W/ 215/75R17.5 LR-H SINGLES (-DEXTER)

- (2) Electric (Spring)

TAIL OPTIONS

- Split / Spreader Gate*

OTHER OPTIONS

- 1 Pair D-Rings
- 1 Hydraulic Monster Jack™ Includes Front Toolbox Light Bar w/4 Lights (GN Only)
- Top Riser Toolbox
- Upgrade to Single 10k Jack (Bumper Pull)
- Solar Battery Charger
- 6" Taller GN Riser
- 9,990 G.V.W.R.
- 12"oc Crossmembers
- Power Up/Down & Gravity Down Upgrade
- Mount Only for Spare Tire (Under Frame)
- Tarp kit (Pull Bar) 8 x 18ft
- Spare Tire and Mount (Bumper Pull) (Under Frame)
- Bulldog 2-speed Jacks (12,000 lb.)



19" FOLD DOWN SIDES

The 96" Deckover Dump has 19" sides that easily fold down to facilitate side loading of pallets and cargo. This feature increases the potential uses of this trailer significantly.



SCISSOR LIFT STANDARD

The 96" Deckover Dump comes with a 5" x 17" cylinder and scissor lift standard. The scissor lift significantly increases the strength and stability of the trailer.

TANDEM DUAL DUMP (DD)



Lengths: 16' - 20'



12" I-BEAM FRAME

Length	Axles	Est. Base Weight [†]
16'	2 x 10,000 lbs	7,800 lbs / 3,538 kg
18'	2 x 10,000 lbs	8,320 lbs / 3,774 kg
20'	2 x 10,000 lbs	8,840 lbs / 4,010 kg

[†] Weights are estimated for base trailer.
PJ Trailers makes no guarantee regarding the accuracy of estimated weights.

- GVWR: **25,000-28,000 LBS.** ▪ AXLE: **TANDEM & TRIPLE (2 X 10-12,000 LBS. AXLE)**
- LENGTH: **16-20'** ▪ CAPACITY: **14.22 YD³ - 17.78 YD³**
- SIDES HEIGHT: **36"** ▪ INSIDE WIDTH: **94"** ▪ BED HEIGHT: **39"** ▪ DUMP ANGLE: **45°**
- COUPLERS: **BUMPER PULL, GOOSENECK & PINTLE** ▪ TIRES: **235/80R16 RADIAL TIRES**

STANDARD FEATURES

- 25,000 lb. G.V.W.R.
- 10,000 lb. x 2 G.A.W.R.
- GN 2 5/16" Ball Bulldog Coupler 25,000 lb
- Safety Chains
- 2 - Drop Leg Jacks (10,000 lb.)
- 2 - Dexter Oil Bath Brake Axles (10,000 lb.)
- 5 Leaf Slipper Spring Suspension
- 8 Dual Wheels, 16" Grey, 8 on 6.5" Bolt Pattern
- 8 - 16" 235/80R16 Radial Tires (3,090 lb)
- Rubrail & Stake Pockets
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- Ladder on Right Side
- Lockable Front Toolbox w/ Chain Holder
- 2 - Way Gate (Barn Doors & Spread Gate)
- 70" Ramps w/ Holders
- 4 Flushmount D-Rings
- 45° Dump Pitch
- 12VDC Hydraulic Pump
- 10 Ton Scissor Lift
- 12" x 19 lb. I-Beam Main Frame, Riser & Neck
- 2 x 6 x 1/8" Square Tubing Outer Deck Frame
- 3" Channel Crossmembers 16
- 10-ga. Steel Bed
- 96" Wide Bed
- 12ga. Steel Sides
- 36" High Removable Sides
- DOT Approved Flushmount Lifetime LED Lights
- All-Weather Wiring Harness (7-way RV)
- Sand Blasted, Acid Washed, Powder Coated
- Interstate (TM) Deep Cycle Battery
- 110V Integrated Trickle Charger
- Dual 5" x 25 1/2" Hyd. Cylinder w/Hoist
- 5 year Dexter Axle Warranty

AVAILABLE OPTIONS

* denotes a standard feature

COUPLER OPTIONS

- BP 2 5/16" Adj Rigid Mount (25,000 lb.) w/Tbx
- 3" Pintle Eye - Face-mount (36,000 lb.) w/Tbx
- GN 2 5/16" Round (25,000 lb.)*
- GN 2 5/16" Square (25,000 lb.)
- GN 2 5/16" Round (30,000 lb.)
- GN 2 5/16" Square (30,000 lb.)
- GN 2 5/16" Round (30,000 lb.) w/ 6" Longer Tube

AXLE OPTIONS

10,000# AXLES (DEXTER)

- (2) Electric (Spring)*

10,000# W/14 PLY LR-G DUAL T&W (DEXTER)

- (2) Electric (Spring)

12,000# AXLES (DEXTER)

- (2) Electric (Spring)
- (2) Elec/Hyd Disc (1,600 PSI Pump) (Spring)

12,000# W/14 PLY LR-G DUAL T&W (DEXTER)

- (2) Electric (Spring)

TAIL OPTIONS

- Barn Doors
- Split / Spreader Gate*

OTHER OPTIONS

- 1 Pair D-Rings
- HD 25k Jost 2x Jacks
- 2 Hydraulic Monster Jacks™
- 1 Side-mount Toolbox 45"x17 1/2"
- 1 Side-mount Toolbox 72"x17 1/2"
- Solar Battery Charger
- 6" Taller GN Riser
- Under Frame Tie Down Flat
- 4ft Removable Sides
- 12" oc Crossmembers
- Power Up/Down & Gravity Down Upgrade
- 6ft Removable Sides
- 4" Ratchets every 4ft w/ Slide Track
- 6" Axle Spread (Longer Equalizer)
- 22 lb. I-Beam Main Frame, Riser & Neck
- Tarp Kit 100" (Uninstalled)
- Bulldog 2-speed Jacks (12,000 lb.)
- Grain Chute

12" I-BEAM



12" HD I-BEAM FRAME

The DD dump features a heavy duty 10" I-beam frame for maximum strength, backed by our 3-year frame warranty.



PREMIUM HYDRAULIC SYSTEMS

A dump trailer is only as good as its hydraulic components, and we choose to use the finest parts available. Our pumps are shielded in a steel locking toolbox for protection against the elements.

DUMP OPTIONS GUIDE

POWDER COAT COLOR OPTIONS:

ACTUAL COLOR MAY VARY, CHECK SPECIFIC MODEL PAGE FOR AVAILABLE COLORS



BLACK



GREY



DESERT TAN



WHITE



RED



TRACTOR ORANGE

COUPLER OPTIONS:



GOOSENECK 2 5/16"



A-FRAME
BUMPER PULL 2" - 2 5/8"



BUMPER PULL 2 5/16"



PINTLE EYE

OTHER OPTIONS:




SIDE EXTENSIONS



TARP KIT



3', 4' & 6' REMOVABLE SIDES
(DD DUMP ONLY)



SOLAR CHARGER



REMOVABLE
DECK ON THE NECK



REAR SUPPORT STANDS



2-SPEED JACKS



HYDRAULIC MONSTER JACKS



STILLWELL 7K
HYDRAULIC JACK



SINGLE 10K JACK



EXTRA D-RINGS



SPARE TIRE AND MOUNT



SPARE TIRE MOUNT



6" SCISSOR LIFT CYLINDER

SOME OPTIONS NOT SHOWN, PLEASE VIEW PRODUCT PAGE FOR A LIST OF ALL OPTIONS



PJ TRAILERS

- #1 Professional Grade Open Trailer Manufacturer
- Broad Line of Dumps, Flatdecks, Utilities, Carhaulers, Tilts & Equipment Trailers
- Over 300 Independent PJ Trailers Dealer Locations in the US & Canada

Visit Us Online at www.pjtrailers.com



YouTube